

# JDS NDRC NOSTALGIA PRO STOCK

February 10, 23 Update

## **BODY:**

1967-1979 American model kit based, resin, or promo bodies in 1/24 or 1/25 scale.  
Corvettes, or sports cars prohibited. No concept, or "show car" bodies.  
No Lexan or Styrene Vacuum formed bodies.

## **BODY MODIFICATIONS:**

No modification to body, other than grinding out inside of body to lightening.  
No "wedge" cutting to lower body.  
Enlarging rear wheel wells allowed to clear tires  
Must follow the original shape of the opening  
No cutting of any kind allowed on the bodies  
Wheelie bar upright clearance slots in lower rear valance/bumper. Complete opening of rear valance around uprights not allowed

## **WINGS-REAR SPOILERS**

Wings, and spoilers allowed but must be representative of era of body used  
Flat-angle spoilers with spill plates not allowed

## **HOOD SCOOPS:**

All cars must run a scoop that replicates the style representative of the era  
All scoops must be a minimum of 1/8" tall, and 1/2" wide.  
Scoops must be mounted forward of the windshield  
Aero Style scoops prohibited, Cowl induction prohibited  
Hemi Style" hood scoops are allowed on 1967-1970 Chrysler product bodies only

## **WINDOWS/GLASS:**

Must have clear, or lightly tinted windows  
Lexan replacement allowed  
Optional Clear or slightly tinted Lexan or styrene may be used for passenger, and driver windows  
No "blacked out" windows

## **INTERIOR:**

3D driver and full interior card mandatory  
Interior card must be painted  
Detailing of driver optional but highly encouraged

## **CHASSIS:**

Inline Chassis only  
Axle bearings allowed

## **FRONT WHEELS/TIRES:**

5/8" (.625) minimum, 3/4" (.750) maximum diameter rims  
Front plastic, resin or 3D printed wheels allowed  
Wheels must be painted, or chrome plated  
MINIMUM front tire diameter is .935

**REAR WHEELS/TIRES:**

True scale diameter wheels only

"Pencil hub" wheels not allowed.

Plastic, resin, 3D printed, and non-metallic rear wheels are NOT allowed

Rear tires. Height: 1 1/8" (1.125) minimum height. Width: 1/2" (.500) minimum

**WHEELIE BARS:**

Total length cannot exceed five (5) inches from the centerline of the rear axle to the centerline of the wheelie wheel axle.

**MOTOR:**

Pro Slot PS-2200, or PS-2200-BP "Crazy Horse" S16D

Blueprinting allowed

Must retain original "Poly Neo" magnets

Bearings are NOT permitted

Soldering bushing to can is permitted

Any springs and brushes allowed

Armature shims/spacers allowed

Centering of magnets allowed

No shimmering of magnets

Must retain OEM end bell and hardware

Any end bell securing screws maybe used

No shunt wires

Crimping" of can is not allowed

Comm Drops Okay

No Freezing permitted

**Motor Replacement Parts:**

The only replacement armature is Pro Slot PS-917

The only replacement end bell is PS-2009

The only replacement end bell hardware is PS-2010

**WEIGHT**

Minimum weight 125 grams

**RACE PROCEDURE:**

Heads-up on a .400 Pro Tree

Single elimination

**POINTS:**

Winner 20 points

Runner up 15 points

Third 10 points

Fourth 5 points

**NOTE:** Prior to the final, Semi Losers will race to determine third and fourth finishing order

**ENTRIES:**

Maximum of two cars per entrant

One entry per car-no double entries

**NOTE:**

All NDRC general rules apply. Rules are subject to change by NDRC with seven-day advance notice. If it doesn't say it's legal, it's not.